



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Bag filter housing

Materials of Construction: 304, 316L stainless steel

Shell O-rings: Silicone rubber, EPDM, Fluorine

Surface finish: 0.3-0.4 micron

Connection of the housing: General purpose bolts or lifting bolts

Connector of the pressure gauge: Threaded Adaptor

Connector of the filter cartridge: 222, 226, or Threaded Adaptor

Connection of the inlet and exhaust: Flange connector or Clamp Coupling

Customized: YES

Product Description:

Yitong stainless steel bag filter is mainly used for coarse filtration and prefiltration, it is easy to operate, high effective, suitable for high flow, high capacity filtering applications. The filter bags inside the filter will be fixed well by the clamp ring, which provide great leakproofness. The 100% 304 or 316 stainless steel structure makes it is corrosive-resistant, and gives a longer service life.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Performance Feature:

- 1 Easy to operate, economical, suitable for high flux situation.
- 2 The spring is used to press the ring of filter bag tightly, make sure the leakproofness between the filter bag and the housing
- 3 The upper-lower path is adopted, the feed method is reasonable, easy to operate.

Application:

Bag filter housing is suitable for the pre-filtration and rough filtration of the fluids with a certain content of solids, usually applied in the high flow rate filtration and security filtration.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Technical Parameter:

Materials of Construction	304, 316L stainless steel
Shell O-rings	Silicone rubber, EPDM, Fluorine
Surface finish	0.3-0.4 micron
Connection of the housing	General purpose bolts or lifting bolts
Connector of the pressure gauge	Threaded Adaptor
Connector of the filter cartridge	222, 226, or Threaded Adaptor
Connection of the inlet and exhaust	Flange connector or Clamp Coupling
Customized	YES

Packing and shipping:



Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications,such as the material,length,micron,adapter,apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q:How longabout your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail:manager@yitong-filter.com

WhatsApp:+86 180 3376 5689

WeChat: +86 180 3376 5689