



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Glass Fiber pleated filter cartridge

Filter area: 0.45 m²/10 inch

Filter membrane: Glass Fiber

Guide layer: PP

Inner support、end cap、shell: PP


Seal ring material: Silicone,Viton,EPDM,PTFE

Max.working temperature: ≤80℃

Max. working pressure drop: 0.4Mpa/23℃ / 0.21Mpa/80℃

Product Description:

Yitong Glass fiber pleated filter cartridges are constructed from robust glass fibre and polypropylene filtration layers, offering removal ratings from 0.5 to 5 micron absolute. It is suitable for absolute removal of unwanted particulates and for prefiltration to membrane filters. It incorporates a polypropylene prefiltration layer, combined with a high dirt capacity glass fibre media. This has the effect of longer service life, improved operating costs and smaller process footprint. These filter cartridges are suitable for applications ranging from bioburden reduction and the clarification of a wide range of process liquids and end products.



Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail:manager@yitong-filter.com

WhatsApp:+86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Performance Feature:

- 1 Excellent hydrophilic ability, no need to wet before applying it.
- 2 Extremely low dissolved matter.
- 3 Great chemical compatibility
- 4 Perfect chemical interception ability
- 5 It can be autoclaved

Application:

- 1 Prefiltration of high viscous liquids and compressed gas
- 2 Prefiltration of serum and blood related products.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Technical Parameter:

Cartridge structure	Filter area	0.45 m ² /10 inch
	Filter membrane	Glass Fiber
	Guide layer	PP
	Inner support、end cap、shell	PP
	Seal ring material	Silicone,Viton,EPDM,PTFE
Working situation	Max.working temperature	≤80°C
	Max. working pressure drop	0.4Mpa/23°C
		0.21Mpa/80°C

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail:manager@yitong-filter.com

WhatsApp:+86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Packing and shipping:



FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications, such as the material, length, micron, adapter, apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q: How long about your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689