



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Stainless steel filter housing

Materials of Construction: 304, 316L stainless steel

Shell O-rings: Silicone rubber, EPDM, Fluorine

Surface finish: 0.3-0.4 micron

Connection of the housing: flange connector or Clamp Coupling

Connector of the pressure gauge: Threaded Adaptor

Connector of the filter cartridge: 222, 226, or Threaded Adaptor

Connection of the inlet and exhaust: flange connector or Clamp Coupling

Customized: YES

Product Description:

Yitong Stainless Steel Filter Housings are industrial filter housings that accommodate different diameter filter cartridges and conform to Chinese national standard. These rugged housings offer all stainless steel construction and have great leakproofness. These Filter Housings are compatible with a wide range of fluids. Various cartridge types can be used including Wound, Melt Blown, Pleated, Carbon, Resin Bonded, Stainless Steel and others. The polishing tech is used on the inside and outside surface to avoid the rust problem.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Performance Feature:

- 1 It has various interface for filter cartridge, use the advanced numerical control machinery to process it
- 2 The surface finish outside is 0.4 micron, inside is 0.3 micron.
- 3 Comply with ISO2852 standard, the connector of the pressure gauge is adopted the "R" quick connector with Plane welding.
- 4 The height of the housing is adjustable.

Application:

Prefiltration and clarification filtration of different industries, including pharmacy, chemical, beverage and liquor industries. It is also suited well in the production of sterilizing air in the fermentation system.

Technical Parameter:

Materials of Construction	304, 316L stainless steel
Shell O-rings	Silicone rubber, EPDM, Fluorine
Surface finish	0.3-0.4 micron
Connection of the housing	flange connector or Clamp Coupling
Connector of the pressure gauge	Threaded Adaptor
Connector of the filter cartridge	222, 226, or Threaded Adaptor
Connection of the inlet and exhaust	flange connector or Clamp Coupling
Customized	YES

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Packing and shipping:



FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications, such as the material, length, micron, adapter, apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q: How long about your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689